




Push-Lok B-1 Kits	9 Push-Lok Merchandiser	B-180	Assembly Instructions	82 Series Assembly Instructions	B-181
Push-Lok Hose and Fitting Kits	Push-Lok Ho Fitting Displa				




30182 Male NPTF Pipe - Rigid



#									tional erial
Part	Thread	Hose I.D.	A	A	Н	E	3		Stainless
Number	inch	inch	inch	mm	inch	inch	mm	Brass (B)	Steel (C)
30182-2-4	1/8x27	1/4	1.39	35	7/16	0.64	16	•	•
30182-4-4	1/4x18	1/4	1.57	40	9/16	0.82	21	•	•
30182-4-6	1/4x18	3/8	1.78	45	9/16	0.88	22	•	•
30182-4-8	1/4x18	1/2	1.93	49	5/8	0.88	22	•	
30182-6-6	3/8x18	3/8	1.78	45	11/16	0.88	22	•	•
30182-6-8	3/8x18	1/2	1.93	49	11/16	0.88	22	•	
30182-8-6	1/2x14	3/8	2.03	52	7/8	1.13	29	•	•
30182-8-8	1/2x14	1/2	2.18	55	7/8	1.13	29	•	•
30182-8-10	1/2x14	5/8	2.58	66	7/8	1.13	29	•	
30182-8-12	1/2x14	3/4	2.58	66	7/8	1.13	29	•	
30182-12-8	3/4x14	1/2	2.21	56	3/4	1.16	29	•	
30182-12-10	3/4x14	5/8	2.61	66	1-1/16	1.16	29	•	
30182-12-12	3/4x14	3/4	2.61	66	1-1/16	1.16	29	•	•
30182-16-16	1x11-1/2	1	3.06	78	1-3/8	1.61	41	•	•

31382 Male NPTF Pipe - Swivel




# Part		Hose I.D.	,	A	W		B	Additional Material
Number	inch	inch	inch	mm	inch	inch	mm	Brass (B)
31382-4-4	1/4x18	1/4	1.60	41	9/16	0.85	22	
31382-6-6	3/8x18	3/8	1.79	45	11/16	0.89	23	
31382-8-8	1/2x14	1/2	2.20	56	7/8	1.15	29	
31382-8-10	1/2x14	5/8	3.50	90	7/8	2.05	52	•
31382-12-12	3/4x14	3/4	3.70	94	1-1/4	2.25	57	

O-Ring not compatible with Phosphate Ester fluids.



Female NPTF Pipe - Rigid


# Part	///////// Thread	Hose I.D.	A		H	В		Additional Material
Number	inch	inch	inch	mm	inch	inch	mm	Brass (B)
30282-4-4	1/4x18	1/4	1.56	40	3/4	0.81	21	•
30282-6-6	3/8x18	3/8	1.82	46	7/8	0.92	23	•
30282-8-8	1/2x14	1/2	2.16	55	1-1/16	1.11	28	•



37G82

Female NPSM Pipe - Gasket Joint - Swivel


# Part		//////// Thread	Hose I.D.	A		W	E	3
Number	Gasket	inch	inch	inch	mm	inch	inch	mm
37G82-4-4	07G-4	1/4x18	1/4	1.55	39	11/16	0.80	20
37G82-4-6	07G-4	1/4x18	3/8	1.70	43	11/16	0.80	20
37G82-6-6	07G-6	3/8x18	3/8	1.75	44	7/8	0.85	22
37G82-8-8	07G-8	1/2x14	1/2	2.07	53	1	1.02	26
37G82-8-10	07G-8	1/2x14	5/8	2.47	63	1	1.02	26
37G82-12-12	07G-12	3/4x14	3/4	2.54	65	1-1/4	1.09	28



30382


Male JIC 37° - Rigid

# Part		////// hread	Hose I.D.	Δ	A		В	1	Additional Material
Number		inch	inch	inch	mm	inch	inch	mm	Brass (B)
30382-4-4	1/4	7/16x20	1/4	1.56	40	1/2	0.81	21	
30382-5-4	5/16	1/2x20	1/4	1.59	40	9/16	0.84	21	
30382-6-6	3/8	9/16x18	3/8	1.78	45	5/8	0.88	22	•
30382-8-8	1/2	3/4x16	1/2	2.06	52	3/4	1.01	26	
30382-10-10	5/8	7/8x14	5/8	2.62	67	7/8	1.17	30	
30382-12-12	3/4	1-1/16x12	3/4	2.72	69	1-1/8	1.27	32	



Textile gasket included with fitting.


Female JIC 37° - Swivel



#	_^	·····	0							itional terial
Part Number	٦	Γhread inch	Hose I.D. inch	inch		W inch	inch	mm	Brass (B)	Stainless Steel (C)
30682-4-4	1/4	7/16x20	1/4	1.52	39	9/16	0.77	20	•	•
30682-5-4	5/16	1/2x20	1/4	1.58	40	5/8	0.83	21	•	
30682-5-6	5/8	1/2x20	3/8	1.72	44	5/8	0.82	21	•	
30682-6-4	3/8	9/16x18	1/4	1.61	41	11/16	0.86	22	•	
30682-6-6	3/8	9/16x18	3/8	1.75	44	11/16	0.85	22	•	•
30682-6-8	3/8	9/16x18	1/2	1.90	48	11/16	0.85	22	•	
30682-8-6	1/2	3/4x16	3/8	1.87	47	7/8	0.97	25	•	
30682-8-8	1/2	3/4x16	1/2	2.02	51	7/8	0.97	25	•	•
30682-10-8	5/8	7/8x14	1/2	2.14	54	1	1.09	28	•	
30682-10-10	5/8	7/8x14	5/8	2.54	65	1	1.09	28	•	•
30682-12-12	3/4	1-1/16x12	3/4	2.65	67	1-1/4	1.20	30	•	•
30682-16-16	1	1-5/16X12	1	2.77	70	1-3/8	1.32	34	•	

33782

Female JIC 37° - Swivel - 45° Elbow - Short Drop



# Part	Thread		Hose I.D.	A		E		H	W	E	3
Number		inch	inch	inch	mm	inch	mm	inch	inch	inch	mm
33782-4-4	1/4	7/16x20	1/4	1.74	44	0.39	10	7/16	9/16	0.99	25
33782-6-6	3/8	9/16x18	3/8	1.99	51	0.43	11	1/2	11/16	1.09	28
33782-8-8	1/2	3/4x16	1/2	2.58	66	0.55	14	5/8	7/8	1.53	39
33782-10-10	5/8	7/8x14	5/8	3.03	77	0.65	17	3/4	1	1.58	40

33982


Female JIC 37° - Swivel - 90° Elbow - Short Drop

# Part		······································	Hose I.D.	Α		E		<u>H</u>	⊘		В
Number		inch	inch	inch	mm	inch	mm	inch	inch	inch	mm
33982-4-4	1/4	7/16x20	1/4	1.55	39	0.83	21		9/16	0.80	20
33982-6-6	3/8	9/16x18	3/8	1.85	47	0.91	23		11/16	0.95	24
33982-8-8	1/2	3/4x16	1/2	2.33	59	1.09	28	5/8	7/8	1.28	33
33982-10-10	5/8	7/8x14	5/8	2.88	73	1.24	31	3/4	1	1.43	36
33982-12-12	3/4	1-1/16x12	3/4	3.26	83	1.81	46	7/8	1-1/4	1.81	46

34182

Female JIC 37° - Swivel - 90° Elbow - Long Drop


#		^	0								
Part	Т	hread	Hose I.D.	A		E		Н	W	E	3
Number		inch	inch	inch	mm	inch	mm	inch	inch	inch	mm
34182-4-4	1/4	7/16x20	1/4	1.79	45	1.80	46	7/16	9/16	1.04	26
34182-6-6	3/8	9/16x18	3/8	1.97	50	2.18	55	1/2	11/16	1.07	27





Male SAE 45° - Rigid


# Part	Thread		Hose I.D.	A	1	H	В	ı
Number	ir	nch	inch	inch	mm	inch	inch	mm
30482-4-4B	1/4	7/16x20	1/4	1.51	38	7/16	0.76	19
30482-5-4B	5/16	1/2x20	1/4	1.61	41	9/16	0.86	22
30482-6-6B	3/8	5/8x18	3/8	1.84	47	5/8	0.94	24
30482-8-8B	1/2	3/4x16	1/2	2.15	55	3/4	1.10	28



30882

Female SAE 45° - Swivel


# Part Number		hread	Hose I.D.	A inch			B	mm	Additional Material Brass (B)
30882-4-4	1/4	7/16x20	1/4	1.52	39	9/16	0.77	20	• `
30882-5-4	5/16	1/2x20	1/4	1.58	40	5/8	0.83	21	•
30882-6-6	3/8	5/8x18	3/8	1.81	46	3/4	0.91	23	•
30882-8-6	1/2	3/4x16	3/8	1.87	47	7/8	0.97	25	•
30882-8-8	1/2	3/4x16	1/2	2.02	51	7/8	0.97	25	•
30882-10-10	5/8	7/8x14	5/8	2.54	65	1	1.09	28	•
30882-12-12	3/4	1-1/16x14	3/4	2.65	67	1-1/4	1.20	30	•



37782

Female SAE 45° - Swivel - 45° Elbow

# Part		·//·//	Hose I.D.	A		E		$\bigcap_{\mathbf{H}} \bigcirc_{\mathbf{W}}$		E	3
Number		inch	inch	inch	mm	inch	mm	inch	inch	inch	mm
37782-4-4	1/4	7/16x20	1/4	1.79	45	0.33	8	7/16	9/16	1.04	26
37782-6-6	3/8	5/8x18	3/8	2.08	53	0.39	10	1/2	3/4	1.18	30
37782-8-8	1/2	3/4x16	1/2	2.58	66	0.55	14	5/8	7/8	1.53	39




37982

Female SAE 45° - Swivel - 90° Elbow

# Part		//////\\	Hose I.D.	Α	\	E		Н	\bigcirc	E	3
Number	inch		inch	inch	mm	inch	mm	inch	inch	inch	mm
37982-4-4	1/4	7/16x20	1/4	1.60	41	0.83	21	7/16	9/16	0.85	22
37982-6-6	3/8	5/8x18	3/8	1.98	50	0.85	22	1/2	3/4	1.08	27
37982-8-8	1/2	3/4x16	1/2	2.33	59	1.09	28	5/8	7/8	1.28	33


B-171



Notch in nut signifies 45° flare.




Male Inverted SAE 45°- Swivel



# Part	Thread		Thread Hose I.D.		A I		$\bigcap_{\mathbf{H}} \bigcap_{\mathbf{W}}$		В	
Number	j	nch	inch	inch	mm	inch	inch	inch	mm	
32882-3-4	3/16	3/8x24	1/4	2.15	55	3/8	3/8	1.40	36	
32882-4-4	1/4	7/16x24	1/4	2.15	55	7/16	7/16	1.40	36	
32882-5-4	5/16	1/2x20	1/4	2.31	59	7/16	1/2	1.56	40	
32882-6-6	3/8	5/8x18	3/8	2.58	66	1/2	5/8	1.68	43	
32882-8-8	1/2	3/4x18	1/2	2.82	72	5/8	3/4	1.77	45	
32882-10-10	5/8	7/8x18	5/8	3.34	85	3/4	7/8	1.89	48	

36782


Male Inverted SAE 45° - Swivel - 45° Elbow



#										_	
Part	Т	hread	Hose I.D.	A		-		Н	W	E	5
Number		inch	inch	inch	mm	inch	mm	inch	inch	inch	mm
36782-4-4	1/4	7/16x24	1/4	1.92	49	0.63	16	7/16	7/16	1.17	30
36782-6-6	3/8	5/8x18	3/8	2.64	67	0.94	24	1/2	5/8	1.74	44

36982


Male Inverted SAE 45° - Swivel - 90° Elbow



# Part			Hose I.D.	Δ		E		н	s	Е	3
Number	inch		inch	inch	mm	inch	mm	inch	inch	inch	mm
36982-4-4	1/4	7/16x24	1/4	1.99	51	1.56	40	7/16	7/16	1.24	31
36982-5-4	5/16	1/2x20	1/4	2.17	55	1.65	42	7/16	1/2	1.42	36
36982-6-6	3/8	5/8x18	3/8	2.30	58	1.69	43	1/2	5/8	1.40	36

32982

Female Inverted SAE 45° - Rigid



#		·····					_	
Part	Th	read	Hose I.D.	P	1	Н	E	3
Number	i	nch	inch	inch	mm	inch	inch	mm
32982-4-4B	1/4	7/16x24	1/4	1.19	30	1/2	0.44	11
32982-5-4B	5/16	1/2x20	1/4	1.25	32	9/16	0.50	13
32982-6-6B	3/8	5/8x18	3/8	1.44	37	3/4	0.54	14
32982-8-8B	1/2	3/4x18	1/2	1.62	41	7/8	0.57	14




3JC82

Female Seal-Lok® - Swivel - Short

ISO 12151-1 - SWSA

												litional aterial
	Thread	Hose I.D.	A		C		С Н		B		Brass	Stainless
inch		inch	inch	mm	inch	mm	inch	inch	inch	mm	(B)	Steel (C)
1/4	9/16x18	1/4	1.40	36	0.32	8	9/16	11/16	0.65	17		•
3/8	11/16x16	3/8	1.59	40	0.38	10	11/16	13/16	0.69	18		•
3/8	11/16x16	3/8	1.59	40	0.38	10	19mm	22mm	0.69	18		
1/2	13/16x16	3/8	1.65	42	0.38	10	13/16	15/16	0.76	19		
1/2	13/16x16	1/2	1.80	46	0.43	11	13/16	15/16	0.75	19		•
5/8	1x14	5/8	2.40	61	0.53	13	15/16	1-1/8	0.95	24		
3/4	1-3/16x12	3/4	2.63	67	0.57	14	1-1/8	1-3/8	1.18	30		•
1	1-7/16x12	1	2.61	66	0.58	15	1-3/8	1-5/8	1.16	29	•	•
	1/4 3/8 3/8 1/2 1/2 5/8 3/4	Thread inch 1/4 9/16x18 3/8 11/16x16 3/8 11/16x16 1/2 13/16x16 1/2 13/16x16 5/8 1x14 3/4 1-3/16x12	Thread inch Hose I.D. inch 1/4 9/16x18 1/4 3/8 11/16x16 3/8 11/16x16 3/8 1/2 13/16x16 3/8 1/2 13/16x16 1/2 5/8 1x14 5/8 3/4 1-3/16x12 3/4	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch inch inch inch inch inch	Thread inch inch inch mm inch mm inch inch inch inch inch mm inch inch inch inch inch mm inch inch inch inch inch inch inch inch




When measuring overall length to the end of the nut, B+C dimensions must be used to calculate cut-off allowance.

3J782

Female Seal-Lok® - Swivel - 45° Elbow

ISO 12151-1 - SWE45


# Part			Hose I.D.	Δ		E		\bigcirc	В	3
Number		inch	inch	inch	mm	inch	mm	inch	inch	mm
3J782-4-4	1/4	9/16x18	1/4	1.74	44	0.39	10	11/16	0.99	25
3J782-6-6	3/8	11/16x16	3/8	1.99	51	0.43	11	13/16	1.09	28
3J782-8-8	1/2	13/16x16	1/2	2.41	61	0.59	15	15/16	1.36	35



3J982

Female Seal-Lok® - Swivel - 90° Elbow - Short Drop ISO 12151-1 - SWES90

# Part	_	/////// Thread	Hose I.D.	Α	\	E		W	Е	3
Number		inch	inch	inch	mm	inch	mm	inch	inch	mm
3J982-4-4	1/4	9/16x18	1/4	1.55	39	0.83	21	11/16	0.80	20
3J982-6-6	3/8	11/16x16	3/8	1.85	47	0.91	23	13/16	0.95	24
3J982-6-8	3/8	11/16x16	1/2	2.09	53	0.91	23	13/16	1.04	26
3J982-8-6	1/2	13/16x16	3/8	1.94	49	1.14	29	15/16	1.04	26
3J982-8-8	1/2	13/16x16	1/2	2.16	55	1.14	29	15/16	1.11	28
3J982-10-10	5/8	1x14	5/8	2.76	70	1.26	32	1-1/8	1.31	33
3J982-12-12	3/4	1-3/6x12	3/4	3.27	83	1.89	48	1-3/8	1.82	46




3J182

Female Seal-Lok® - Swivel - 90° Elbow - Long Drop

ISO 12151-1 - SWEL90

#			0							
Part	1	hread	Hose I.D.	A	`	E		W	Е	
Number		inch	inch	inch	mm	inch	mm	inch	inch	mm
3J182-6-6	3/8	11/16x16	3/8	1.85	47	2.13	54	13/16	0.95	24
3J182-8-8	1/2	13/16x16	1/2	2.16	55	2.52	64	15/16	1.11	28

See Accessories for O-Rings.








	L A J
	В
_	
R	-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
<u></u>	
	- D- _

#	Ø	0								ditional aterial
Part	Ŕ	Hose I.D.	<i>F</i>	4		כ	E	3	Brass	Stainless
Number	inch	inch	inch	mm	inch	mm	inch	mm	(B)	Steel (C)
33482-4-4	1/4	1/4	1.89	48	1.02	26	1.14	29	•	•
33482-5-4	5/16	1/4	1.93	49	1.08	27	1.18	30	•	
33482-6-6	3/8	3/8	2.23	57	1.22	31	1.33	34	•	•
33482-8-8	1/2	1/2	2.16	55	0.97	25	1.11	28	•	•
33482-10-10	5/8	5/8	2.62	67	1.00	25	1.17	30	•	
33482-12-12	3/4	3/4	2.62	67	1.00	25	1.17	30	•	•

38282


Push-Lok Union



# Part	Hose I.D.			Additional Material
Number	inch	inch	mm	Brass (B)
38282-4-4	1/4	1.80	46	•
38282-6-6	3/8	2.15	55	•
38282-8-8	1/2	2.51	64	•
38282-10-10	5/8	3.31	84	•
38282-12-12	3/4	3.31	84	•
38282-16-16	1	3.31	84	•

3D082

Male Metric L - Rigid - (24° Cone)



# Part			Hose I.D.	A	A	Он	E	3
Number		mm	inch	inch	mm	mm	inch	mm
3D082-6-4	6	M12x1,5	1/4	1.34	34	12	0.55	14
3D082-8-4	8	M14x1,5	1/4	1.38	35	14	0.59	15
3D082-10-6	10	M16x1,5	3/8	1.57	40	17	0.63	16
3D082-12-6	12	M18x1,5	3/8	1.61	41	19	0.67	17



► Hose

U Fittings 82 Series

C Equipment


D Accessories

Technical

31D82

Male Standpipe Metric L - Rigid


# Part	R	Hose I.D.	A		ise i.b.)		В
Number	mm	inch	inch	mm	inch	mm	inch	mm	
31D82-6-4	6	1/4	1.73	44	0.87	22	0.98	25	
31D82-8-4	8	1/4	1.73	44	0.87	22	0.98	25	
31D82-10-6	10	3/8	1.93	49	0.91	23	1.02	26	
31D82-12-6	12	3/8	1.93	49	0.91	23	1.06	27	
31D82-15-8	15	1/2	2.17	55	0.98	25	1.10	28	
31D82-18-10	18	5/8	2.64	67	1.02	26	1.10	28	
31D82-22-12	22	3/4	2.72	69	1.10	28	1.22	31	



39282

Female BSP Parallel Pipe - Swivel - (60° Cone)

# Part	///////// Thread		A	A	C	;	\bigcirc	В	3	Additional Material
Number	inch	inch	inch	mm	inch	mm	mm	inch	mm	Brass (B)
39282-4-4	1/4x19	1/4	1.34	34	0.22	6	17	0.55	14	
39282-6-6	3/8x19	3/8	1.50	38	0.26	7	19	0.55	14	•
39282-8-8	1/2x14	1/2	1.77	45	0.28	7	27	1.06	27	
39282-12-12	3/4x14	3/4	2.13	54	0.35	9	36	1.42	36	




When measuring overall length to the end of the nut, B + C dimensions must be used to calculate cut-off allowances.

3D982

Male BSP Parallel Pipe - Rigid - (60° Cone)

# Part	Hose I.D.		Ą	H	E	3
Number	inch	inch	mm	mm	inch	mm
3D982-2-4	1/4	1.42	36	14	0.63	16
3D982-4-4	1/4	1.61	41	19	0.83	21
3D982-4-6	3/8	1.77	45	19	0.83	21
3D982-6-6	3/8	1.77	45	22	0.87	22
3D982-8-8	1/2	2.09	53	27	0.98	25
3D982-8-10	5/8	2.44	62	27	0.94	24
3D982-12-12	3/4	2.56	65	32	1.06	27




Bonded seal required if fitting is used directly in a port. See Accessories Section.

3B282


Female BSP Parallel Pipe - Swivel - 90° Elbow - (60° Cone)

#				4		E	₩ W	E	3
Part Number	Thread inch	Hose I.D.	inch	mm	inch	mm	mm	inch	mm
3B282-4-4	1/4x19	1/4	1.65	42	1.02	26	17	1.02	26
3B282-6-6	3/8x19	3/8	2.09	53	1.18	30	19	1.18	30
3B282-8-8	1/2x14	1/2	2.56	65	1.57	40	27	1.57	40
3B282-10-10	5/8x14	5/8	2.99	76	1.57	40	30	1.57	40









#	Ø	0				
Part	R	Hose I.D.	<i> </i>	À	E	3
Number	mm	inch	inch	mm	inch	mm
34982-8-4	8	1/4	1.42	36	0.63	16
34982-10-4	10	1/4	1.50	38	0.71	18
34982-12-4	12	1/4	1.57	40	0.79	20
34982-12-6	12	3/8	1.73	44	0.79	20
34982-14-4	14	1/4	1.65	42	0.87	22
34982-14-6	14	3/8	1.85	47	0.91	23
34982-16-6	16	3/8	1.93	49	0.98	25
34982-18-8	18	1/2	2.17	55	1.06	27

AMBanjo Bolt with DIN Metric Thread



#	(·····	\bigcirc	
Part		R Thread	н	Copper Washer
Number		mm	mm	(2)
AM-03	8	M8x1	12	853009-8
AM-04	10	M10x1	14	853009-10
AM-06	12	M12x1.5	17	853009-12
AM-08	14	M14x1.5	19	853009-14
AM-10	16	M16x1.5	22	853009-16
AM-13	18	M18x1.5	24	853009-18
AM-16	22	M22x1.5	27	853009-22
AM-20	26 M26x1.5		32	853009-26
AM-30	30	M30x1.5	36	853009-30

Two (2) copper washers per bolt must be ordered separately.




3CA82

Female Metric L - Swivel - (24° Cone with O-Ring)

ISO 12151-2 - SWS


# Part	//////// Thread		Hose I.D.	A		W	Е	
Number	inch		inch	inch	mm	mm	inch	mm
3CA82-8-4	8	M14x1,5	1/4	1.42	36	17	0.67	17
3CA82-10-6	10	M16x1,5	3/8	1.57	40	19	0.67	17
3A82-10-6B	10	M16x1,5	3/8	1.57	40	19	0.67	17
3A82-12-6	12	M18x1,5	3/8	1.57	40	22	0.67	17
3A82-15-8	15	M22x1,5	1/2	1.73	44	27	0.71	18
3A82-22-12	22	M30x2	3/4	2.28	58	36	0.83	21



3CF82

Female Metric L - Swivel - 90° Elbow - (24° Cone with O-Ring) ISO 12151-2 - SWE


# Part			Hose I.D.	A	A	E		W	ı	3
Number		inch	inch	inch	mm	inch	mm	mm	inch	mm
3CF82-8-4	8	M14x1,5	1/4	1.65	42	1.26	32	17	0.91	23
3CF82-10-6	10	M16x1,5	3/8	1.93	49	1.38	35	19	1.06	27
3CF82-10-6B	10	M16x1,5	3/8	1.93	49	1.38	35	19	1.06	27
3CF82-12-6	12	M18x1,5	3/8	1.93	49	1.42	36	22	1.06	27
3CF82-15-8	15	M22x1,5	1/2	2.28	58	1.61	41	27	1.26	32
3CF82-22-12	22	M30x2	3/4	3.46	88	2.17	55	36	2.01	51



3C482


Female Metric L - Swivel - 45° Elbow - (Ball Nose) ISO 8434-1

#			0	A		E		\bigcirc	E	3
Part Number	. '	inch	Hose I.D.	inch	mm	inch	mm	mm	inch	mm
3C482-8-4B	8	M14x1,5	1/4	2.01	51	0.63	16	17	1.26	32
3C482-10-6B	10	M16x1,5	3/8	2.28	58	0.71	18	19	1.38	35
3C482-15-8B	15	M22x1,5	1/2	2.68	68	0.75	19	27	1.61	41
3C482-22-12	22	M30x2	3/4	3.46	88	0.91	23	36	2.05	52



3C582

Female Metric L - Swivel - 90° Elbow - (Ball Nose) ISO 8434-1




# Part					Hose I.D. A		Ę		W	Е	3
Number		inch	inch	inch	mm	inch	mm	mm	inch	mm	
3C582-8-4B	8	M14x1,5	1/4	1.65	42	1.14	29	17	0.91	23	
3C582-10-6B	10	M16x1,5	3/8	1.93	49	1.30	33	19	1.06	27	
3C582-15-8B	15	M22x1,5	1/2	2.36	60	1.54	39	27	1.34	34	
3C582-22-12B	22	M30x2	3/4	3.46	88	1.97	50	36	2.01	51	

3C382

Female Metric L - Swivel - (Ball Nose)

ISO 8434-1



#			0				_	
Part	Thread		Hose I.D.	Ą		W	B	
Number	inch		inch	inch	mm	mm	inch	mm
3C382-8-4B	8	M14x1,5	1/4	1.42	36	19	0.63	16
3C382-10-6B	10	M16x1,5	3/8	1.50	38	19	0.59	15
3C382-15-8B	15	M22x1,5	1/2	1.65	42	27	0.59	15
3C382-22-12B	22	M30x2	3/4	2.09	53	36	0.67	17

